

## **S p e c i f i c a t i o n**

<b>Product:</b>	<b>Hot Rubber Melter.</b>
<b>Capacity:</b>	<b>150 Litres – Approx. 1 Drum</b>
<b>Model:</b>	<b>3 Phase Fully Electric</b>
<b>Power:</b>	<b>415-volt 3 phase – 32 amps (load 20 kW).</b>
<b>Plug:</b>	<b>3 pin female neutral &amp; earth into Melter – 3 pin male neutral &amp; earth into power source.</b>
<b>Control Panel:</b>	<b>Digital – Temperature Control.</b>
<b>Burner:</b>	<b>Electric heating element.</b>
<b>Main Frame:</b>	<b>40 x 40 x 2mm RHS.</b>
<b>Pan:</b>	<b>5mm plate.</b>
<b>End Plates:</b>	<b>Profiled 6mm.</b>
<b>Outside Case Sheet:</b>	<b>2mm.</b>
<b>Outlet:</b>	<b>Profiled.</b>
<b>Forklift Locating Sleeves:</b>	<b>Channel.</b>
<b>Drive:</b>	<b>415/30/3 phase motor – gearbox.</b>
<b>Insulation:</b>	<b>High temperature Rockwool dense slab.</b>
<b>Stirrer Shaft:</b>	<b>40mm BMS.</b>

**Stirrer Shaft**

**Bearings:** 40mm Pillar block.

**Casters:** 2 No. 200mm fixed  
2 No. 200mm swivel/braked.

**Lifting Eyebolts:** M20 metric collared.  
**D Shackles:** 3.25-ton green pin safety.

**Dimensions:**

<b>Length:</b>	<b>1980mm</b>
<b>High:</b>	<b>1560mm</b>
<b>Width:</b>	<b>790mm</b>
<b>Loading Height:</b>	<b>930mm</b>
<b>Weight:</b>	<b>554kg</b>

This specification and any drawings/images related to it are the sole Copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent.

WJ Horrod Ltd reserves the right to alter, change or modify this equipment to improve it without prior notice.



Image above does not display 1 drum unit and is for reference purposes only.