



S p e c i f i c a t i o n

Product:	Hot Air Rubber Melter
Capacity:	2 Drum – 110 imperial gallons approx.
Type:	Digital Thermostat control – 110-volt electric drive
Casters:	2 No. 200mm swivel/braked cast iron 2 No. 200mm fixed cast iron
Construction:	
Main Body Frame:	40 x 40 x 2mm SHS
Outside Case:	2mm mild steel sheet
Link/Gearbox Arms:	Profiled
Pan:	Half diameter type – 5 mm mild steel plate
Pan End Plates:	Profiled 6mm mild steel plate
Insulation:	High temperature Rockwool dense slab - encased
Drive:	110-volt electric motor coupled to gearbox
Power:	110 volts – 32amp
Stirrer Shaft:	60 mm bright mild steel round



Stirrer Shaft Bearings:	2 No. heavy duty self-aligning 60 mm pillar blocks
Agitation:	Oscillating continuous paddle
Firing:	LPG propane gas
Burner:	Open nozzle type, 2 No. 50 mm
Burner Tubes:	4.000 NB SCH40 304 stainless steel pipes
Flue Return Tubes:	114.0 x 6mm mild steel
Material Outlet:	Gate type
Temperature Control:	Electric thermostat control
Temperature Gauge:	Digital
Lifting Facilities:	4 No. certified metric collared eyebolts 4 No. certified 3.25t shackles
Overall Shipping Dimensions:	
Length:	1960 mm
Width:	1270 mm
Working Height:	1025 mm
Overall Height:	1570 mm
Weight:	900 kg



This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent.

WJ Horrod Ltd reserve the right to alter, change or modify this equipment to improve it without prior notice.

