



## S p e c i f i c a t i o n

Product:	Trailer Mounted Thermostat Control Bitumen Boiler.
Model:	SMS4
Capacity:	25 & 50 gallon.
Boiler Specification:	
Outside Case:	16 gauge hot rolled sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skins, seams fully welded.
Case Sub Frame:	50 x 25 x 2.5 RHS 40 x 40 x 3mm RSA
Removable Pan:	3mm hot rolled sheet fully welded both inside and out.
Lid:	Fixed (bolt down) anti-splash type with loading chute.
Burner:	Stainless steel ribbon bar burner c/w with pilot.
Thermostat:	Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.
Material Outlet:	1" plug cock type.
Firing:	LPG propane gas.



Trailer Specification: Unbraked.

Chassis:

Main Chassis: 80 x 40 x 4 RHS.

Main Suspension: Un-braked 750kg unit.

Wheels: 4 Stud 5½" PCD wheels fitted with 165 R 13 8PR 96N tyres.

Mudguard: Steel 13"

Tow Couple: Option of tow eye or ball head.

Jockey Wheel: 42mm smooth jockey wheel assembly.

Trailer Lights: Radex rear lamp 5 function plug in left – Radex rear lamp plug in c/w number plate lamp – c/w 7 pin plug – Independent red triangle reflectors.

Finish: Colour of your choice – subject to colour – one coat Selemix.  
Please be advised Highways yellow required 3 coats and there is an additional charge for this.

This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent of WJ Horrod Ltd.

WJ Horrod Ltd also reserve the right to alter, change or modify this product to improve it without prior notice.

 **72 Years of Excellence**  
**Horrods**  
Engineering ~ Safety ~ Efficiency



1 Leaway off Lea Bridge Road London E10 7QW [www.wjhorrod.co.uk](http://www.wjhorrod.co.uk)

©W J Horrod Ltd 2022