

S p e c i f i c a t i o n

Product:	Hot Rubber Melter
Capacity:	3 Drum
Model:	Fully Electric
Power:	415-volt 3 phase – 64 amps (load 40kW)
Control Panel:	Digital – Temperature control
Drive:	3 phase motor/gearbox
Power Lead Type:	3 pin female neutral & earth into melter – 3 pin male neutral & earth into power source
Burner:	2 x electric heating elements
Capacity:	540 litres approx.
Main Frame:	40 x 40 x 2mm RHS
Pan:	Semi-circle – 5mm mild steel plate
Stirrer Shaft:	60mm bright mild steel
Stirrer Shaft Bearings:	2 No. heavy duty self-aligning 60mm pillar blocks
Agitation:	Oscillating continuous paddle
End Plates:	Profiled – 6mm
Outside Case Sheet:	2mm mild steel sheet



Forklift Locating Sleeves:	160mm x 80mm x 5mm RHS
Outlet:	Profiled – 2-piece door and frame
Insulation:	High temperature Rockwool dense slab
Casters:	2 No. 200mm fixed 2 No. 200mm swivel/brake Load capacity 500kg per caster
Lifting Eyebolts:	4 X M20 metric collared eye bolt – 1.5 ton
D Shackles:	4 x 3.25-ton green pin safety.
Power lead Length:	20 metre 415 volt.
Dimensions:	Length: 2540mm Height: 1700mm Width: 1250mm Weight: 1063kg

This specification and any drawings related to it are the sole Copyright of W J Horrod and must not be passed to a third party without prior consent.

WJ Horrod reserves the right to alter, change or modify this equipment to improve it without prior notice.

74 Years of Excellence
Horrods
Engineering ~ Safety ~ Efficiency



**1 Leaway off Lea Bridge Road London E10 7QW www.wjhorrod.co.uk
©W J Horrod Ltd 2023**