



S p e c i f i c a t i o n

Product:	Hot Air Rubber Melter
Capacity:	4 Drum - 220 imperial gallons approx.
Type:	Digital thermostat control – 110-volt electric drive
Casters:	2 No. 200mm swivel/braked cast iron 2 No. 200mm fixed cast iron
Construction:	
Main Body Frame:	40 x 40 x 2mm SHS
Outside Case:	2mm mild steel sheet
Link/Gearbox Arms:	Profiled.
Pan:	Half diameter type – 5 mm mild steel plate
Pan End Plates:	Profiled – 6mm mild steel plate
Insulation:	High temperature Rockwool dense slab - encased
Drive:	110-volt electric motor coupled to gearbox
Power:	110-volts – 32amp
Stirrer Shaft:	60 mm bright mild steel round
Stirrer Shaft Bearings:	2 No. heavy duty self-aligning 60 mm pillar blocks



Agitation:	Oscillating continuous paddle
Firing:	LPG propane gas
Burner:	Open nozzle type, 2 No. 50 mm
Burner Tubes:	4.000 NB SCH40 304 stainless steel pipes
Flue Return Tubes:	114.0 x 6mm mild steel
Material Outlet:	Gate type
Temperature Control:	Digital Electric thermostat control.
Temperature Gauge:	Digital
Lifting Facilities:	4 No. certified M20 metric collared eyebolts 4 No certified 3.25t shackles

Overall Shipping Dimensions:

Overall length:	2860mm
Width:	1225mm
Overall height:	1700mm
Working height:	1065mm
Weight:	1100kg

All sizes and weights are approx.

This specification and any drawings/images related to it are the sole Copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent.

WJ Horrod Ltd also reserves the right to alter, change or modify this equipment to improve it without prior notice.

 74 Years of Excellence
Horrods
Engineering ~ Safety ~ Efficiency

